

- Breathes out water vapors
- Long lasting effects
- Consistent
- One time solution

**Specially formulated cement based plaster premix which offers easy passage for wall dampness**



**Salient Properties**

- Formulated as preventive treatment
- Efflorescence free, strong surface

**Major Advantages**

- Provides riddance from side effects of dampness & Efflorescence on wall surfaces
- Provides durable, permanent solution

OSMOPLAST is an indigenous, self curing, sand free ready mix mortar formulation from Perlcon which makes damp wall free of moisture by releasing the vapors into the environment. Since it does not allow seeped water to get accumulated within plaster surface, it prevents stain formations as well as flaking and peeling of paints on your beautiful walls. Osmoplast surface can be finished with cement/water based paints or with Perlcon Colorplast.

Packing	40 Kg.
---------	--------



**1**  
Excessive wall / Paint Deterioration due to prolong Dampness



**2**  
Expose brick work Wherever Damped spots are found by removing entire plaster layer & allow bricks to get dry for 2-3 days



**4**  
Now apply 10-15 mm thk Perlcon **OSMOPLAST** readymix mortar and match the adjacent plaster surfaces



**3**  
First apply an plaster under coat of 6-8 mm using perlcon "**SANDFREE**" ready mix plaster mortar and allow it dry for 2-3 days



**5**  
Allow, OSMOPLAST layer to dry for 4-6 days and now wall is ready to receive water/Cement base Paint